

WHEN ACCURATE SCREENING MATTERS!

FEATURES

- Sanitary magnesium alloy construction
- 10-35 Sq. ft. of screen area
- 2,3 or 4 Separations
- Up to 50,000 lbs. Per hour capacity
- Only 4 sq. ft. of floor space required
- Quick change screen
- Optional deck port hole for easy inspections



MODEL

CS 1

FOR ACCURATE SIZING OF DRY, FREE-FLOWING MATERIALS

EASY TO INSTALL

The Model CS-1 sifter is shipped as a complete unit with motor, drive and screen cloth installed. Simply bolt it to the floor or other level support, attach inlet and outlet sleeves, connect it to your power source and this sifter is ready to build profits

EASY TO DISMANTLE

All screen stack components are readily removable. No special tools or skills are required. After removing external rods, deck cover and individual screen decks can be lifted off easily and quickly

EASY TO INSPECT

Inspection goes hand in hand with the cleanup operation – and assembling the machine afterward is as easy as the dismantling procedure




EASY TO CLEAN

You can clean with brush, air, water or cleaning solution. Removable screen cloth inserts snap out quickly, exposing all internal surfaces

PLENUM BAGS, CARTRIDGE FILTERS, RECLAIM SIFTERS, POLY BALLS



GUM RUBBER TUBING, CUSTOM DUST BAGS, OEM BAGHOUSE FILTERS



SIFTER PARTS & SERVICE, INC.

YOUR ULTIMATE SOURCE FOR SIFTERS, SCREENS, FABRIC FILTERS & TRANSFER SLEEVES

Phone: 800.367.3591 • Fax: 813.991.9700 • Info@sifterparts.com • sifterparts.com